

MAXPROBE XL

Pipeline Inspection System

The MaxProbe XL is packed with innovative and helpful features to enhance user efficiency and provides everything you need to carry out a professional drainage survey.



Technical Data - Maxprobe XL

Cable length	100 m
Meterage counter	yes
Driving Force	Manual (push Rod)
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Battery	Li-ion (9hrs running time)
Operating Temp	-10°C to +50°C
Charging Temp	0°C to +40°C
Weight	Reel – 38.5kg Box – 5.5kg approx.
Dimensions	Reel – 660 x 480 x 998 mm Box – 360 x 290 x 160 mm
LCD size	10.4" (diagonal)
Resolution	800 x 600 RGB (SVGA)
LCD viewing angle	85° Typical
IP Rating	IP64 – open / closed
Storage	32Gb HHD standard x2 USB 2.1 x1 SD x1 Ethernet
Software	WinCan Embedded
Output	800 x 600 SVGA. DE15 socket
Video Format	MPEG4
Image Format	JPEG



Issue Date July 2016
Subject to change without prior notice.

FOCUSING ON THE FUTURE



Scanprobe Techniques Ltd
Unit 11, Kenley Trade Park, Old Barn Lane, Kenley, Surrey CR8 5AU
Tel: 020 3253 2001 Fax: 020 8660 5074

www.scanprobe.com

