

MAXPROBE

Pipeline Inspection System



The MaxProbe is packed with innovative and helpful features to enhance user efficiency and provides everything you need to carry out a professional drainage survey.

Technical Data - Maxprobe	
Cable length	50 / 60 m
Meterage counter	yes
Driving Force	Manual (push Rod)
Voltage	12v DC / 230v AC / 115v AC
Current	Ex Power Supply - 1.7A Max
Battery	Li-ion (9hrs running time)
Operating Temp	-10°C to +50°C
Weight	Reel - 23.5kg Box - 5.5kg approx.
Dimensions	Reel - 1010 x 415 x 625 mm Box - 360 x 290 x 160 mm
LCD size	10.4" (diagonal)
Resolution	800 x 600 RGB (SVGA)
LCD viewing angle	85° Typical
IP Rating	Box (IP64 - open / closed) Camera (IP68)
Storage	32Gb HHD standard
Data Export	x2 USB 2.1 x1 SD x1 Ethernet WiFi / 4G
Software	WinCan Embedded / WinCan Web
Output	800 x 600 SVGA. DE15 socket
Video Format	MPEG4
Image Format	JPEG
Nominal pipe size	50mm - 200mm
Pipe bend accessibility	70mm approx.
Camera Dimension	44mm OD
Illumination	Light Emitting Diode
Focal extent	40mm - ∞
Iris control	Fixed
Light sensitivity	0.01 LUX
Location frequency	33kHz / 512Hz



Issue Date May 2017
Subject to change without prior notice.

FOCUSING ON THE FUTURE



Scanprobe Techniques Ltd
Unit 11, Kenley Trade Park, Old Barn Lane, Kenley, Surrey CR8 5AU
Tel: 020 3253 2001 Fax: 020 8660 5074

www.scanprobe.com

