



X-40 Datasheet

The **Scanprobe X-40** is the most versatile pipeline inspection system on the market. Designed to be used with your personal mobile device on Android/iOS, a fully customised **X-Range Tablet**, or a bespoke **Maxprobe** CCU. Made from light weight aluminium and incorporating a 30mm, fully traceable camera head, that has the flexibility to navigate traps and toilet bends, the **X40** truly is the next generation of inspection cameras.

The **X-40** combines technology, software and robust designs to create an easy-to-use, light-weight, battery operated (up-to 6hrs) and multifaceted product. With an **X-40** on your inventory, you'll wonder how you managed to survey with out one.



Rod Length	40 metres / 130 foot
Rod Diameter	8.6mm
Weight	12.6 kg
Coiler Dimensions	W 296mm, H 483mm, L 392mm
Camera Diameter	30mm
Pipe Use	50mm to 150mm Ø, 2" to 6" Ø
Sonde Locator	33kHz or 512Hz (optional)
Meterage Counter	Yes
Self-levelling camera	Yes
Camera Resolution	PAL: 720Hx576V
Light Source	12 LED
Operating Temperature	-10°C - +50°C
Output	USB-C
Battery type	Li-ion
Battery Life	Up to 6 hours
Capacity	6.52Ah
Charge Current	1.5A
Nominal Voltage	7.4V
Charging Options	12V & 240V
IP Rating	Camera: IP68, Coiler: IP54
Approvals	CE and UKCA



Connectivity

